LIGHTMOODS

RGB Flat LED Neon Ribbon Light

υv

Resistant

FLRGB-24V-60

Beam


Angle

A color changing linear LED product, looks similar to neon glass. Suitable for many installations including outdoor, indoor, signage, architerctural and a whole lot more!



IK08






Bending

Diameter

Flame

Resistant





Solvent

Resistant

Saltwater


IP68





| al Data | | |
|-----------|--------------|---|
| | FLRGB-24V-60 | |
| oltage | DC24V | |
| er/mtr | 12W | |
| ntr | 60LEDs | |
| ice | 1.67cm | |
| ng Unit | 6LEDs (10cm) | |
| is Length | 10m | |
| | IP68/IP40 | |
| | nl Data | FLRGB-24V-60oltageDC24Vor / mtr12Wottr60LEDsottr1.67cmong Unit6LEDs (10cm)ottr10m |


Candle Power Distribution



Connection Diagram for Injection Molded Light

DO-160G

tested 🔰



CCUL) US LISTED CE ROHS 👿 🚣



Palm Coast, Florida, USA / Los Angeles, California, USA / Pribram, Czech Republic / Birmingham, U.K. / Kuala Lumpur, Malaysia / Mumbai, India Email: christian@aveoengineering.com / Web: www.aveoengineering.com

LIGHTMOODS

RGB Flat LED Neon Ribbon Light

FLRGB-24V-60

A color changing linear LED product, looks similar to neon glass. Suitable for many installations including outdoor, indoor, signage, architerctural and a whole lot more!






DC input

| Beam Angle | Bending Diameter |
|-------------------|---------------------|
| 160° | D:12cm |
| $\langle \rangle$ | |

Pov Ler Ene








Saltwater IP68 IK08 Resistant Protection Protection

| latching Table for Power and Length | | | | | | | | | |
|-------------------------------------|------|-----------|------|------|------|------------|------|------|--|
| ower | 35W | 60W | 100W | 120W | 150W | 180W | 240W | 320W | |
| ength | 2.5m | 4.5m | 7.5m | 9.0m | 10m | 13.5m | 18m | 20m | |
| nergizing Way | DC | input 💶 🗐 | | | | DC input 🕳 | | | |
| | | 01/02 | 2 | | | | 01 | 02 | |

| Customized Length of Injection Molded Light | | | | | | |
|---|----------|----------|----------|----------|----------|----------|
| | Length 1 | Length 2 | Length 3 | Length 4 | Length 5 | Length 6 |
| Length | 10cm | 20cm | 50cm | 100cm | 200cm | 500cm |

| Photometric Data | | |
|------------------|----------------|---------|
| Article No. | FLRGB-24V-60 | |
| LED Type | SMD | |
| Beam angle | 160° | |
| Color | CCT/Wavelength | Lumen/m |
| Red | 620-630nm | >20lm |
| Green | 520-530nm | >75lm |
| Blue | 460-470nm | >15lm |
| White | | >110lm |
| | | |

Illuminance Characteristics





Palm Coast, Florida, USA / Los Angeles, California, USA / Pribram, Czech Republic / Birmingham, U.K. / Kuala Lumpur, Malaysia / Mumbai, India Email: christian@aveoengineering.com / Web: www.aveoengineering.com

