

LIGHTMOODS™

Single Color Flat LED Neon Ribbon Light

FLSCRJ-24V-60
FLSCOJ-24V-60
FLSCRJ-230V-72
FLSCOJ-230V-72

The perfect replacement for neon glass. Easy to use, long lasting & durable. Suitable for many projects and installations including indoor, outdoor, signage & architectural. The color jacket ensures that colors are visible in direct sunlight.



Beam Angle



Bending Diameter



Flame Resistant



UV Resistant



Solvent Resistant







Saltwater Resistant



IP68 Protection




IK08 Protection



Technical Data

Article No.	FLSCRJ-230V-72	FLSCOJ-230V-72	FLSCRJ-24V-60	FLSCOJ-24V-60
Color	Red	Green/Blue/Yellow	Red	Green/Blue/Yellow
Working Voltage	AC230V	AC230V	DC24V	DC24V
Rated Power / mtr	8W	12W	6.5W	10.6W
LED Qty/mtr	72LEDs	72LEDs	60LEDs	60LEDs
LED Distance	1.39cm	1.39cm	1.67cm	1.67cm
Min. Cutting Unit	72LEDs (1m)	72LEDs (1m)	10LEDs (16.7cm)	6LEDs (10cm)
Continuous Length	100m	80m	15m	10m
IP Rating	IP65/IP40	IP65/IP40	IP68/IP40	IP68/IP40

Connection Diagram for Injection Molded Light



LIGHTMOODS™

Single Color Flat LED Neon Ribbon Light

FLSCRJ-24V-60
FLSCOJ-24V-60
FLSCRJ-230V-72
FLSCOJ-230V-72

The perfect replacement for neon glass. Easy to use, long lasting & durable. Suitable for many projects and installations including indoor, outdoor, signage & architectural. The color jacket ensures that colors are visible in direct sunlight.



Beam Angle



Bending Diameter



Flame Resistant



UV Resistant



Solvent Resistant



Saltwater Resistant



IP68 Protection



IK08 Protection



Customized Length of Injection Molded Light

	Length 1	Length 2	Length 3	Length 4	Length 5	Length 6	Length 7
Length (Green/Blue/White)	10cm	20cm	50cm	100cm	200cm	500cm	1000cm
Length (Red/Amber)	16.7cm	33.3cm	50cm	100cm	200cm	500cm	1000cm


Photometric Data

Article No.	FLSCRJ-230V-72 and FLSCOJ-230V-72	
LED Type	SMD	
Beam angle	160°	
Color	CCT/Wavelength	Lumen/m
Red	620-630nm	>30lm
Green	520-530nm	>75lm
Blue	460-470nm	>8lm
Yellow1	574±1.5nm	>150lm
Yellow2	578±1.5nm	>150lm
Yellow3	582±1.5nm	>150lm

Photometric Data

Article No.	FLSCRJ-24V-60 and FLSCOJ-24V-60	
LED Type	SMD	
Beam angle	160°	
Color	CCT/Wavelength	Lumen/m
Red	620-630nm	>90lm
Green	520-530nm	>132lm
Blue	460-470nm	>14lm
Yellow1	574±1.5nm	>200lm
Yellow2	578±1.5nm	>200lm
Yellow3	582±1.5nm	>200lm

Candle Power Distribution



Illuminance Characteristics

