



Specification

Operating Voltage Range:	9-36VDC
Output Power – Landing:	20.5W
Output Power – Taxi:	9.6W
Input Current (at 25°C) – Landing:	0.86A @28V
Input Current (at 25°C) –Taxi:	0.40A @28V
Intensity – Landing White Beam:	80,000 cd
Lens – Landing Beam:	9°
Ambient Temperature:	from -40°C to +85°C from -40°F to +185°F
Transient Voltage:	2 second +80V
Under-Voltage Lockout:	+9VDC, not more
Over-Voltage Lockout:	+36VDC, not less
Color:	White finish Black finish Chrome finish
Weight:	Approx 700g
Waterproof, Dust-proof, Shock-proof, Vibration-proof:	Yes
Pacifica Narrow White	AVE-PF2NW-D01
Pacifica Narrow Blue	AVE-PF2NB-D01
Pacifica Narrow IR	AVE-PF2NI-D01
Pacifica Middle White	AVE-PF2MW-D01
Pacifica Middle Blue	AVE-PF2MB-D01
Pacifica Middle IR	AVE-PF2MI-D01
Pacifica Wide White	AVE-PF2WW-D01
Pacifica Wide Blue	AVE-PF2WB-D01
Pacifica Wide IR	AVE-PF2WI-D01

Dimensional Drawing

